

Configuration Details

Dienstag, 26. Juli 2011

ATP Art. Nr. 405 255 358
Char Lynn 158-3975

Search Criteria/ Model Code:
MT0096AA02AD0000000002A0A

CODE	LIST PRICE	FEATURE	DESCRIPTION
M	0	PRODUCT	MOTOR
T0	0	SERIES	T SERIES MOTOR
096	323.3	DISPLACEMENT	158 CM3/R [9.6 IN3/R]
AA	4.1	MOUNTING TYPE	2 BOLT STD - 82.50 [3.248] DIA. X 3.05 [.120] PILOT, 13.59 [.535] DIA. MOUNTING HOLES ON 106.35 [4.187] DIA. B.C.
02	7.1	OUTPUT SHAFT	25.4 [1.00] DIA. SAE 6B SPLINE, .250-20 UNC-2B HOLE IN SHAFT END
AD	8.2	PORT TYPE	MANIFOLD PORTS (M8 X 1.25-6H MOUNTING HOLES)
0	0	CASE FLOW OPTIONS	NONE SPECIFIED
0	0	GEROLER OPTIONS	NONE
0	0	SHAFT OPTIONS	NONE
00	0	SEAL OPTIONS	STANDARD SEALS
0	0	SPEED SENSOR OPTIONS	NONE
0	0	VALVE OPTIONS	NONE
00	0	SPECIAL FEATURES (HARDWARE)	NONE SPECIFIED
2	5.1	SPECIAL ASSEMBLY INSTRUCTIONS	FLANGE ROTATED 90 DEGREES
A	0	PAINT/PACKAGING OPTIONS	PAINTED LOW GLOSS BLACK
0	0	CUSTOMER ID./NAMEPLATE	NONE SPECIFIED
A	0	DESIGN CODE	ONE (1)